[Lead2pass New Free Lead2pass Cisco 352-001 VCE And PDF Instant Download (381-400)

2017 October Cisco Official New Released 352-001 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! After purchasing the dumps for the 352-001 Exam from Lead2pass, I had no doubt that I'd easily pass the exam. Bundle of thanks to Lead2pass for helping me pass the exam without any troubles. Following questions and answers are all new published by Cisco Official Exam Center: https://www.lead2pass.com/352-001.html QUESTION 381What is the definition of the FCAPS framework? A. an ISO framework that establishes a model for network management and contains guidelines for managing objects, the management database, and the application entityB. a five-volume framework for service management that covers design, transition, and delivery of service, and from which the ISO 20000 was developedC. a series of tools for process improvement that uses statistical methods to reduce defects in processes and manufacturingD. a framework for enterprise architecture that provides a comprehensive approach for designing, planning, implementing, and governing an enterprise information architectureE. a framework for enterprise IP Address Management (IPAM) based on the IANA trusted IP lease allocation schemeAnswer: A QUESTION 382What are three tools for ongoing monitoring and maintenance of a voice and video environment? (Choose three.) A. active monitoring via synthetic probes to measure loss, latency, and jitterB. passive monitoring via synthetic probes to measure loss, latency, and jitterC. flow-based analysis to measure bandwidth mix of applications and their flowsD. flow-based analysis with PTP time-stamping to measure loss, latency, and jitterE. call management analysis to identify CAC failures and call quality issues Answer: ACE QUESTION 383In an MPLS-based network, there is a link that constantly flaps. This flapping makes the network constantly reconverge and causes it to become unstable. Which two technologies can be deployed to resolve the design failure? (Choose two.) A. IP Event DampeningB. BFDC. Carrier DelayD. IP Routing Protocol Route Purge Answer: AC QUESTION 384Refer to the exhibit. This OSPF network has just been deployed with four areas, but the hub-and-spoke area frequently flaps. You must fix this design failure. Which two reasons describe why the implementation of link-state summarization will minimize the effect of the instability in this network? (Choose two.) A. It lowers CPU utilization on ABR routers.B. It allows for a more scalable network.C. It separates the data center area from the hub-and-spoke area.D. It runs a partial SPF on the campus area when any link of the hub-and-spoke flaps.E. It minimizes the number of prefixes that are advertised to other areas. Answer: CD QUESTION 385While designing a security solution, which three requirements would make you decide to deploy an IPS sensor in inline mode? (Choose three.) A. The solution should be resistant to sensor failure.B. The solution should allow for stream normalization.C. The solution should not impact jitter and latency for voice traffic.D. The solution should allow for signature-based pattern matching.E. The solution should allow denying packets inline. Answer: BDE QUESTION 386Refer to the exhibit. Assume that no multicast optimization is done on LAN switches A and B. Which two features can be used to optimize multicast traffic forwarding in this situation? (Choose two.) A. Enable IGMP snooping querier on both switches.B. Configure a static MAC entry for the multicast server.C. Disable IGMP snooping on both switches.D. Disable the IGMP query election process.E. Enable PIM snooping on both switches. Answer: AC QUESTION 387Refer to the exhibit. You are designing an MPLS network with Layer 3 VPNs, where the traffic path must be the same in both directions inside the MPLS network to ensure that symmetric routing occurs. The sites are connected to two PE routers. Which two design considerations will allow you to achieve this symmetric routing? (Choose two.) A. When MPLS TE is used, the bidirectional TE tunnel automatically provides symmetric routing.B. The MPLE TE tunnels should be set up in both directions so that the same path is used.C. There should not be any equal cost paths for IGP inside the MPLS backbone, the IGP routing should use the same path in both directions, and the BGP routing does not matter.D. There should not be any equal cost paths for BGP inside the MPLS backbone, the BGP routing should use the same path in both directions, and the IGP routing does not matter.E. There should not be any equal cost paths for the IGP and the BGP inside the MPLS backbone, and both IGP and BGP routing should use the same path in both directions. Answer: BE QUESTION 388You are designing an IEEE 802.1X solution for a customer, where the network supports a large number of IP phones and printers. You plan to configure MAC address bypass for the phones and printers. What is your primary design and security concern? A. the additional AAA traffic on the networkB. the placement of the AAA serverC. the potential of MAC address spoofingD. the scaling of the MAC address database Answer: C QUESTION 389When you design a network that uses IPsec, where can you reduce MTU to avoid network fragmentation? A. on both ends of the TCP connectionB. on the side closest to the clientC. on the side closest to the serverD. in the WAN Answer: A QUESTION 390What is a characteristic of traffic shaping? A. It minimizes traffic transmission intervals.B. It remarks excess packets above the committed rates.C. It delays and can drop excess traffic.D. It classifies traffic based on certain characteristics. Answer: C QUESTION 391What is the purpose of dynamically created tunnels using IPv6 multicast? A. multicast source registration to the RPB. bypass of the RPF check to the

RPC. transport of all IPv6 multicast traffic to the RPD. first-hop router registration to the RP Answer: D QUESTION 392Which ISAKMP feature could be used within your design recommendation to reduce device CPU load in a small scale setup for known active ISAKMP security associations? A. main modeB. IKEv2C. Dead Peer Detection (DPD)D. Security Parameter Index (SPI) Answer: C QUESTION 393Acme Corporation wants to minimize the risk of users plugging unauthorized switches and hubs into the network. Which two features can be used on the LAN access ports to support this design requirement? (Choose two.) A. BPDU GuardB. PortFastC. Loop GuardD. Root GuardE. DTP Answer: AD QUESTION 394Which two OSPF network type combinations can you use in the design of a Phase 3 DMVPN that requires spoke-to-spoke direct traffic? (Choose two.) A. hub as point-to-multipoint and spokes as non-broadcastB. hub as point-to-multipoint and spokes as point-to-pointC. hub as broadcast and spokes as non-broadcastD. hub as point-to-point and spokes as point-to-point Answer: BC QUESTION 395Which mechanism can you use to improve network performance over PPPoE, IPsec, and GRE networks? A. Path MTU DiscoveryB. Simple Service Discovery ProtocolC. ICMP Router Discovery ProtocolD. Bidirectional Forwarding Detection Answer: A QUESTION 396 Which VPN technology supports multivendor interoperability on a network design? A. VTIB. DMVPNC. Easy VPND. IPsec VPN Answer: D QUESTION 397A customer with a dedicated Frame Relay network plans to move its circuits onto a service provider converged MPLS network. Instead of moving to Ethernet access links right away, the customer wants to tunnel the Frame Relay information across the converged network. In which way is QoS information transmitted across an AToM pseudowire when tunneling Frame Relay traffic? A. QoS information cannot be transported through a pseudowire and is dropped.B. QoS information is preserved in the Frame Relay header and encapsulated into the pseudowire frame.C. QoS information is carried in a control word that is attached to the MPLS frame.D. QoS information is translated into ToS bits in the Ethernet header. Answer: C QUESTION 398Which multicast technology provides a large, many-to-many connectivity for a new application while minimizing load on the existing network infrastructure? A. Bidirectional PIMB. PIM Sparse ModeC. Any-source MulticastD. Source Specific Multicast Answer: A QUESTION 399You are redesigning an OSPF v2 network and must migrate some links. You are concerned that there are different subnet masks. Which link type will still form an OSPF adjacency even if there are subnet mask mismatches? A. broadcastB. point-to-multipointC. non-broadcastD. point-to-point Answer: D QUESTION 400To meet specific business requirements, QoS-marked traffic must be sent over a dedicated link.Which technology fulfills this requirement? A. MPLSB. Q-in-Q tunnelingC. policy-based routingD. traffic policing Answer: C I understood all of the 352-001 questions very easily. I scored 96% on my first try. I am definitely going to spread the dump among friends and colleagues. Keep up the great work. 352-001 new questions on Google Drive: https://drive.google.com/open?id=0B3Syig5i8gpDaUphM0lMOWRjUU0 **2017 Cisco 352-001** exam dumps (All 510 Q&As) from Lead2pass: https://www.lead2pass.com/352-001.html [100% Exam Pass Guaranteed]